



WOOD NAILER

1'-6"

1" MIN.
BELOW
BLOCKING

GRAVEL

- SPECIFIED METAL PARAPET CAP
- CONTINUOUS SHEET MEMBRANE LINER
- CONTINUOUS TAPERED WOOD SHIM (E.G., BEVELED CEDAR SIDING)
- SEAL TOP OF FLASHING WITH A 3-COURSE OF SPECIFIED MASTIC AND REINFORCEMENT FABRIC HIGH-DOMED, CAPPED, GASKETED FASTENERS AT (APPROX. 18" O.C.)
- FASTENERS APPROX. 8" O.C.
- EXTENSION OF FIELD PLIES ABOVE HEAD OF CANT (NOT SHOWN FOR CLARITY)
- SPECIFIED MEMBRANE BASE FLASHING (8" MIN. TO 14" MAX. HEIGHT)
- GRAVEL GUARD
- SPECIFIED PLANTING
- SOIL
- 2-PLY MODIFIED BITUMEN MEMBRANE W/ WATER RETENTION SYSTEM. (FAMOGREEN RET CU-P4) FAMOBIT P4 BASE SHEET
- PROTECTION BOARD (FAMOFLOOR INSULATION MATS)
- THERMAL INSULATION
- ROOF DECK

METAL PARAPET CAP AND BASE FLASHING

SECTION

08-010K

NTS